

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/045194 A1

(51) International Patent Classification⁷: **E21D 20/02**,
E21B 33/12

(21) International Application Number:
PCT/AU2003/001468

(22) International Filing Date:
7 November 2003 (07.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant and

(72) Inventor: **BUXTON, Sean, Peter** [AU/AU]; 22 Salisbury
Street, Somerton Park, S.A. 5044 (AU).

(74) Agent: **TURONEK, Mary, Louise**; Lord & Company, 4
Douro Place, West Perth, W.A. 6005 (AU).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,

CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **PLUG MEMBER**



(57) Abstract: A plug member (10) for retaining grout in a cable bolt hole or a rockbolt hole or inside a rockbolt in underground excavations, comprising a cylindrical cap portion (20) with a means to wedge (26) the cap portion in the hole. The means to wedging means (26) may comprise a plurality of inclined flaps, a continuous resilient skirt, or a tapered bung. The cap portion (20) is provided with at least one port (50) to receive a grout delivery hose. The or each port (50) is comprised of a plurality of flexible flaps (56) moveable between an open position and a closed position. In the closed position the flaps (56) inter-engage to substantially close the port (50) and prevent grout leakage from the hole.